

X-Tech Filler

Filler For Self Putty Applications

OCT 2022

Product Description

X-Tech Filler are high quality processed Filler. They are used with X-Calibur flooring and coatings systems to provide a self Putty application for epoxy paint X-Tech Epoxy seal FLR Versions. They are also used to provide a suitable primed surface for the application of trowel applied epoxy and polyurethane floors by providing a fair faces surface.

Advantages

- Provides Self putty from the paint material
- Dust free
- Single size
- Uniform consistency
- Low resin absorption

Physical Properties

Particle Size	< 200 Microns
---------------	---------------

Packaging

25kg bags.

Shelf Life

Indefinite when stored under shade in dry conditions.

Installation Guidelines

X-Calibur provides detailed method statements on all its products for use in various applications. These must be refereed to prior to starting work. The information below is a summary intended for guidance only.

Application

Apply by Mixing with epoxy painting as X-Tech epoxyseal FLR 110G with ratio (1:(0.5-0.75))(Epoxy : Filler) .Mixing operation will be by adding filler step by step while mixing with epoxy paint in the same Pot. After Mixing use the Final Product to prepare the surface Desfects up to 1 mm from one patch by Knife .Once this is complete the next layer can be applied.

Limitations

Do not spread on to a coating that has exceeded its pot life.

Allow to dry fully 6 hours.

Health and Safety

This product is for industrial use only by trained operatives. It is not considered hazardous in normal use. Please refer to the Material Safety Data Sheet (MSDS) prior to the purchase and use of this product. The MSDS can be obtained via our website www.x-calibur.us

Authorized Technical Specialist

Please note that only X-Calibur Authorized Technical Specialists ('ATSS') are permitted to change any of the information in this data sheet or to provide written recommendations concerning the use of this product. Visit www.x-calibur.us for a full list of X-Calibur ATSS.

Datasheet Validity

X-Calibur makes modifications to its product datasheets on a continuous basis. Please check the datasheet update section on www.x-calibur.us to ensure you have the latest version.

Warranties

X-Calibur supplies products that comply with the properties shown on the current datasheets. In the unlikely event that products supplied are proved not to comply with these properties, then we will replace the non-compliant product or refund the purchase price. X-Calibur does not warrant or guarantee the installation of the products as it does not have control over the installation or end use of the products. Any suspected defects must be reported to X-Calibur in writing within five working days of being detected. X-Calibur Construction Chemistry Inc. **makes no warranty as to merchantability or fitness for a particular purpose and this warranty is in lieu of all other warranties express or implied.** X-Calibur Construction Chemistry Inc. shall not be liable for damages of any sort including remote or consequential damages, down time, or delay.